CCR 2017 Inspection Report AES Puerto Rico

Introduction

PurposeAnnual inspection under the Standards for the Disposal of Coal
Combustion Residuals From Electric Utilities of April 17, 2015
(CCR Rule).Design of the italities of the standard st

ScopeReview of available information and perform a visual inspection of
the AES Puerto Rico (AES-PR) Agremax™ Stockpile Area.

Facility Location

General	AES-PR is located in the south coast of the island of Puerto Rico, about 3.4 miles southwest of downtown Guayama.
Address	AES Puerto Rico Km 142.0 State Road PR-3 Guayama, Puerto Rico 00784

Facility Description

AES-PR is a bituminous coal power plant that generates and sells electricity to the Puerto Rico Electric Power Authority with a total power generation capacity of 520 Megawatts; this represents approximately 15% of the electricity consumed on the island. AES-PR also produces a manufactured aggregate known as AgremaxTM, produced by AES-PR. using its own CCRs. Dry ashes that are not delivered to off-site users are mixed in a pug mill that conditions this CCR to produce AgremaxTM before feeding a conveyor belt used to transfer the mixture to the Stockpile Area at the facility. A stockpile to store the inventory of AgremaxTM is formed by a bulldozer or by dump trucks that are loaded with AgremaxTM by an excavator or front end loader, and the trucks then place the AgremaxTM onto a stockpile. From the Stockpile Area the AgremaxTM is loaded by an excavator or frontend loader into dump trucks, and sent for transport by public highway to off-site users or for disposal. Alternatively, the AgremaxTM can be fed by a bulldozer into a crusher located in the Stockpile Area. The crusher feeds a conveyor to transfer the AgremaxTM to marine vessels in the AES-PR dock area for shipment overseas.

CCR Unit Description

Location	The Stockpile Area is located at the southeast quadrant of the AES-PR site, south of the power plant and east of the limestone storage dome.
Volume	At the time of the inspection the approximate volume of Agremax TM contained in the stockpile was 430,000 tons.
Components	Equipment and facilities of the Stockpile Area include a front-end loader, a bulldozer, a backhoe, a water truck with rear spray nozzles and front water cannon, a broom sweeper, mobile water sprinkler guns, large water hoses, fixed water spray nozzle systems, a truck wheel cleaning station and a feeder / breaker mill. It also includes a three-layer physical containment system to prevent run-on or migration of sediments and runoff from the stockpile. This triple- containment system is composed of a gabion wall, drainage channels made of reinforced concrete and concrete low wall external to an internal road at the south side of the stockpile.

Review of Available Information

The daily inspection records for the October 2016 to July 2017 were reviewed as part of this scope of work. There were no significant issues identified during said inspections and action items have been addressed.

Visua	al Inspection
Date	Thursday July 6, 2017.
Time/Weather	Calm wind and sunny weather conditions prevailed.
Methodology and Limiting Conditions	WRE confirmed the Stockpile Area boundaries and performed a vehicle and walking reconnaissance around its accessible perimeter and terraces but did not look at areas where gaining access may have presented health and/or safety hazards. The Stockpile Area was viewed during afternoon hours for visual evidence of signs of distress or malfunction.
Escort	Gil Rosario of AES provided escort during the visual inspection.

General Observations	The Stockpile Area was operational at the time of the visual inspection. A main work terrace with berms on the edges was observed at the top of the stockpile.
Access Road	The access road was observed to be well graded, with berms on the edges, free of potholes and wetted.
Stockpile Surface / Slopes	No animal burrows were observed. Slopes appeared adequate.
Erosion	Localized rills were observed on the surface of stockpile slopes, they appeared to be related to over-watering by the water sprinkler guns.
Dust	Dust controls, including the broom sweeper, mobile water sprinkler guns, large water hoses and fixed water spray nozzle systems were observed to be in good condition. The water truck was not operational at the time. Some fugitive dust caused by wind was observed on the west slope of the Stockpile at the time of inspection.
Sediment	The gabion wall surrounding the Stockpile Area was observed to be free of sediment and with an adequate and unobstructed setback.
Drainage	The drainage channels surrounding the Stockpile Area were observed to be free of standing water or sediment and unobstructed.
Containment Structures	The low wall appeared to be structurally sound. No gaps or cracks were observed on its concrete surfaces.


-		•		
Co	nr	ПЧ	one	

Changes in Geometry	The size of the Stockpile has increased to an estimated height of 120 feet.
Potential Structural Weaknesses	Based on the visual inspection, no apparent or potential structural weaknesses were observed.
Other Changes	The stockpile slopes have become longer and steeper.

Certification

I hereby certify that I visually inspected and prepared this Report for the Stockpile Area, owned and operated by AES-PR in accordance with the Coal Combustion Residuals Rule 40 CFR 257.84(b). I am a dully-licensed Professional Engineer under the laws of Puerto Rico.

Winston R. Esteves P.E.



License Number

<u>8/31/17</u> License Renewal Date



P.E. Seal